# **SPECIFICATION**

# **TECHNICAL DATA SHEET**

## **300W Outdoor Power Supply**



CET-DY300C

## 1 > General Performance

- ♦ All in one outdoor power station
- ♦ Battery capacity:64000mAh(236.8Wh)
- ♦ Charging methods: DC5.5:16.8/3A
- ♦ Output Ports:DC 12V/5A,USB-A 5V/2A,QC3.0 5V/9V/2A 12V/1.5A,AC inverter switch,AC220V Output socket
- ♦ LED lighting:strong lighting,flashing,SOS rescue;220V working LED:green light:working normally,red light:1.0verload protection 2.0ver temperature protection 3.Short circuit protection 4.0ver-discharge protection.

### 2 > Product Specification


Rated Voltage   210-230V			Output			
Frequency   S0Hz	AC Output	Rated Voltage	210-230V			
Nated Voltage   5V		Rated Power	300W			
Rated Current		Frequency	50Hz			
Rated Current 2A Rated Voltage 5V Rated Current 3A Rated Voltage 9V Rated Current 2A Rated Voltage 12V Rated Current 1.5A Rated Voltage 12V Rated Current 1.5A Rated Voltage 12V Rated Current 1.5A Rated Voltage 12V Rated Current 5A Rated Current 5A LED Lighting LED lights are divided into three gears, strong lighting, flashing, SOS rescue, long press for strong lighting, In Click SOS rescue, In Press Stop or long press to stop.  220V working LED Rated Voltage 16ht: Novrking normally, red light: 1.0 verload protection 2.0 ver temperature protection 3. Short circuit protection 4.0 ver-discharge protection.  POE 5.5 Input Rated Voltage 16.8V Rated Current 1.5A/3A  Rated Capacity 236.8Wh Battery Cell Type Ternary lithium battery Charging Time About 5 hours  General  Storage Enviroment 14F-113F Working Temperature -4T-122F Product Size 200*145*150mm	USB-A Output	Rated Voltage	5V			
Rated Current 3A  Rated Voltage 9V  Rated Current 2A  Rated Voltage 12V  Rated Current 1.5A  Bated Current 5A  Rated Voltage 12V  Rated Current 5A  Rated Voltage 12V  Rated Current 5A  LED Lighting LED lights are divided into three gears, strong lighting, flashing, SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click SOS rescue, long press for strong lighting, in Click Pop, in Click Pop		Rated Current	2A			
Rated Voltage 9Y  Rated Current 2A  Rated Voltage 12V  Rated Current 1.5A  Rated Voltage 12V  Rated Current 5A  LED Lighting LED lights are divided into three gears, strong lighting, flashing, SOS rescue, long press for strong lighting, In Click Pop, in Click SOS rescue, In Press Stop or long press to stop.  LED Lighting Ceren light:working normally, red light: 1. Overload protection 2. Over temperature protection 3. Short circuit protection 4. Over-discharge protection.  POE 5.5 Input Rated Voltage 16.8V  Rated Current 1.5A/3A  Rated Current 1.5A/3A  Battery 236.8Wh  Battery Cell Type Ternary lithium battery  Charging Time About 5 hours  General  Storage Enviroment 14T-113T  Working Temperature -4T-122T  Product Size 200°145°150mm  Product Net weight 2.5kg	QC3.0 Output	Rated Voltage	5V			
Rated Current   2A		Rated Current	3A			
Rated Voltage   12V   Rated Current   1.5A		Rated Voltage	9V			
Rated Current 1.5A  Poc 5.5 Output Rated Voltage 12V  Rated Current 5A  LED Lighting LED lights are divided into three gears, strong lighting, flashing, SOS rescue, long press for strong lighting, In Click SOS rescue, In Press Stop or long press to stop.  220V working LED Green light:working normally, red light: 1.0 verload protection 2.0 ver temperature protection 3. Short circuit protection 4.0 ver-discharge protection.    Input		Rated Current	2A			
Rated Voltage   12V		Rated Voltage	12V			
Rated Current   SA		Rated Current	1.5A			
LED Lighting  LED lights are divided into three gears, strong lighting, flashing, SOS rescue, long press for strong lighting, In Click Pop, in Click SOS rescue, In Press Stop or long press to stop.  220V working LED  Green light:working normally, red light: 1.0verload protection 2.0ver temperature protection 3.5hort circuit protection 4.0ver-discharge protection.  Input  Rated Voltage 16.8V  Rated Current 1.5A/3A  Battery  Rated Capacity 236.8Wh  Battery Cell Type Ternary lithium battery  Charging Time About 5 hours  General  Storage Enviroment 14T-113T  Working Temperature — 4T-122T  Product Size 200*145*150mm  Product Net weight 2.5kg	DC 5 5 Outmut	Rated Voltage	12V			
Tescue, In Press Stop or long press to stop.  220V working LED  Green light:working normally,red light:1.Overload protection 2.Over temperature protection 3.Short circuit protection 4.Over-discharge protection.  Input  Rated Voltage Rated Current  Rated Capacity  Rated Capacity  Battery  Charging Time  Storage Enviroment  Working Temperature  Product Size  Product Net weight  Stop Storage Environment  Product Net weight  Product Net weight  Product Net weight  Product Net weight  Green light:working protection 2.Over temperature protection 3.Short circuit protection 4.Over-discharge protection.  Input  16.8V  Battery  Battery  Battery  Passage  16.8V  1.5A/3A  Protection  1.5A/3A  Battery  Battery  236.8Wh  Ternary lithium battery  About 5 hours  General  14T-113T  4T-113T  4T-112T  Product Net weight  2.5kg	DC 5.5 Output	Rated Current	5A			
DC5.5 Input   Rated Voltage   16.8V	LED Lighting					
Rated Voltage	220V working LED					
Rated Current 1.5A/3A  Battery  Rated Capacity 236.8Wh  Battery Cell Type Ternary lithium battery  Charging Time About 5 hours  General  Storage Enviroment 14T-113T  Working Temperature —4T-122T  Product Size 200°145°150mm  Product Net weight 2.5kg			Input			
Rated Current 1.5A/3A  Battery  Rated Capacity 236.8Wh  Battery Cell Type Ternary lithium battery  Charging Time About 5 hours  General  Storage Enviroment 14T-113T  Working Temperature -4T-122T  Product Size 200*145*150mm  Product Net weight 2.5kg	DC5.5 Input	Rated Voltage	16.8V			
Rated Capacity 236.8Wh  Battery Cell Type Ternary lithium battery  Charging Time About 5 hours  General  Storage Enviroment 14T-113T  Working Temperature -4T-122T  Product Size 200*145*150mm  Product Net weight 2.5kg		Rated Current	1.5A/3A			
Battery Cell Type Ternary lithium battery  Charging Time About 5 hours  General  Storage Enviroment 14T-113T  Working Temperature —4T-122T  Product Size 200°145°150mm  Product Net weight 2.5kg	Battery					
Charging Time         About 5 hours           General           Storage Enviroment         14T-113T           Working Temperature         -4T-122T           Product Size         200*145*150mm           Product Net weight         2.5kg	Rated Capacity		236.8Wh			
General   14T-113T	Battery Cell Type		Ternary lithium battery			
Storage Enviroment         14T-113T           Working Temperature         —4T-122T           Product Size         200°145°150mm           Product Net weight         2.5kg	Charging Time		About 5 hours			
Working Temperature         —4			General			
Product Size 200*145*150mm  Product Net weight 2.5kg	Storage Enviroment		14 <b>T</b> -113 <b>T</b>			
Product Net weight 2.5kg	Working Temperature		-4F-122F			
	Product Size		200*145*150mm			
Certificates 1.CE 2.FCC 3.UL 4.RoHS 5.PSE 6.UN38.3 7.MSDS	Product Net weight		2.5kg			
	Certificates		1.CE 2.FCC 3.UL 4.RoHS 5.PSE 6.UN38.3 7.MSDS			



# **SPECIFICATION**

## **TECHNICAL DATA SHEET**

#### 3 > Product Introduction



- 1. Power/LED light switch
- 2. USB output\*2 5V/2A 9V/2A
- 3. Power input port
- 4. DC out put
- 5. AC inverter switch
- 6. AC switch display light
- 7. AC/220V output socket
- 8. Electric quantity digital display
- 9. LED lighting

## 4 > Packing Information









- 2.User Manual × 1
- 3.Packaging outer box x 1
- 4.AC Adaptor (Including AC Charging Cable) x 1
- 5. Certificate of conformity x 1
- 6. Type C data cable x 1







Item	Quantity	G.W / CTN	Carton Size
CET-DY300C	4 PCS/CTN	11.2kg	510*235*490mm

### 5 > Warranty (1-Year-Limited)

The manufacturer's warranty is void under the following circum

stances but not limited to:

- $\diamondsuit$  Improper or inadequate maintenance or modification.
- ♦ The use of unspecified adapter and accessories.
- ♦ Accident, misuse, abuse, contamination, or other external causes.
- ♦ Damages that occurs as a result of one's failure to follow the instructions.

#### 6 > Company Information

## Camel Electronic Technology Co., Ltd.

Add: No. 40, Dajinzhong Road, Baiyun District, Guangzhou City, Guangdong Province, CN 551040

Tel&WhatsApp: +86-13922158739

Linkedin:linkedin.com/in/艾-李-5b24a1ba

Email: info@camelet.com Official Website: http://www.camelet.com



Camel Electronic Technology Co., Ltd

For reference only, the actual product specifications prevail.  $% \label{eq:control_product} % \label{$